

# PRODUCT INFORMATION BULLETIN

## 900MHz MOBILE ANTENNA

Bracket or Magnetic Mount

### MODELS 49-2101 / 49-2102

#### DESCRIPTION

These mobile antennas are designed to transmit/receive RF signals from any direction. Used with our 900MHz Air-Eagle RF Systems, this antenna will ensure reliable communications when vehicle is stopped *or* in motion.

Available in bracket or magnetic mounting styles.

#### IMPORTANT NOTE!!

 If installing two or more antennas, it is imperative that they be at least 3 feet apart from one another!

#### **INSTALLATION – BRACKET MOUNT**

- Locate the highest available point to mount the bracket, keeping in mind there is only 17 feet of coax to work with. Using the bracket as a template, screw bracket to mounting surface.
- Thread the supplied antenna to the NMO mount on the bracket.
   When properly connected, the antenna should be snug against the mounting surface of the bracket.
- 3. Run the supplied coax cable from the antenna to the transmitter or receiver being installed.
- Connect the TNC-male connector on the coax cable to the TNC-female connector on the transmitter or receiver.

#### **INSTALLATION – MAGNETIC MOUNT**

- Locate the highest available point on your vehicle to attach magnetic mount assembly. The magnet requires a minimum of a 3" diameter FLAT surface area.
- Thread the supplied antenna to the top of the roof mount connector. When properly connected, the antenna should be snug against the mounting surface of the vehicle.
- 3. Run the supplied coax cable from the antenna to the transmitter or receiver being installed.
- 4. Connect the TNC-male connector on the coax cable to the TNC-female connector on the transmitter or receiver.



BRACKET MOUNTED ANTENNA (49-2101)
Shown Above



MAGNETIC MOUNT ANTENNA (49-2102) Shown Above

#### **SPECIFICATIONS**

| P/N 49-2101 - Bracket Mount  |            |
|------------------------------|------------|
| Frequency                    | 902-928MHz |
| Gain dB                      | 3          |
| Height                       | 1.4"       |
| Diameter                     | 2.4"       |
| Coax Length                  | 17'        |
| Connector (Male)             | TNC        |
| P/N 49-2102 – Magnetic Mount |            |
| Frequency                    | 902-928MHz |
| Gain dB                      | 3          |
| Height (Antenna and Mount)   | 1.9"       |
| Antenna Diameter             | 2.4"       |
| Magnetic Mount Diameter      | 3"         |
| Maximum Vehicle Speed for    |            |
| Magnetic Holding Strength    | 150 MPH    |
| Coax Length                  | 12'        |
| Connector (Male)             | TNC        |

## 900MHz MOBILE ANTENNA

**Bracket or Magnetic Mount** 

MODELS 49-2101 / 49-2102

#### **REPLACEMENT PARTS**

| NMO Mount Antenna   | 99-ANT-0028    |
|---|----------------|
| Antenna Bracket for Mounting 49-2101  | 99-ANTBRK-0001 |
| 3/4" Thru-hole Mounting Assembly w/cable & connector (w/o mounting bracket) | 99-ANT-0017    |
| Magnetic Mounting Assembly w/cable & connector                              | 99-ANT-0015    |

DOCUMENT DATE: 11/18/14



105 Bonnie Drive Butler, PA 16002 (724) 283-4681 Fax (724) 283-5939 www.bwieagle.com